

Infield Mix

SDS Number: BLM063 Revision Date: 8/21/2018

Page 1 of 4

SDS

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC

750 LAKE COOK ROAD, SUITE 440

BUFFALO GROVE, IL 60089

Contact: ChemTrec Acct #: CCN792719

Phone: (847) 215-1144 **Fax:** (847) 215-0577

Email: tech@profileproducts.com Internet: www.profileproducts.com

Emergency: Emergency Phone: (800) 424-9300 (ChemTrec)

Product Identifier: Infield Mix SDS Number: BLM063 Revision Date: 8/21/2018

Description: Naturally found red sand/clay blend. Screened at 1/4", blended to create an ideal playable surface. Works well with Turface/SAF Field Conditioners.

2 HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING GHS Hazard Pictograms:



GHS Hazard Statements:

H335 - May cause respiratory irritation

GHS Precautionary Statements:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Inhalation: Lungs.

Skin Contact: Wash with soap and water until clean

Eye Contact: Wash out with water Ingestion: No adverse effect

Crystalline Silica (Quartz) [EPA Hazard Category: Health (Chronic)]

Carcinogen: OSHA - No NTP - Yes (respirable) IARC - Yes

This product contains up to 40% crystalline silica. The International Agency for Research on Cancer (IARC) has stated that there is sufficient evidence of carcinogenicity of crystalline silica to human beings. It was noted that carcinogenicity was not detected in all industrial circumstances studied. The NTP's Sixth Annual Report on Carcinogens include respirable crystalline silica. The Hazard Communication Standard (29CFR 1910.1200) requires that any material



Infield Mix

SDS Number: BLM063 Revision Date: 8/21/2018

Page 2 of 4

containing over 0.1% of a substance reported as a carcinogen in an IARC monograph or the most recent NTP Annual Report on Carcinogens must be identified as a carcinogen. These identifications are for hazard communications only and do not serve as assessments of carcinogenic risk. Crystalline silica is known to cause silicosis. At dust levels below the recommended PEL exposure to the crystalline silica contained in this product should not present a health hazard.

Inhalation of excessive concentrations of any dust, including this material, may lead to lung injury. As formulated, this product is not expected to form appreciable respirable crystalline silica dust from use or attrition. Because application and exposure data indicate exposure to respirable quartz in the normal use of the ingredient within this product which contains crystalline silica, is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV). Adverse effects would not be expected from normal use of this product

NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a



COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
14808607		Silica, crystalline quartz

4 FIRST AID MEASURES

Inhalation: Move to fresh air.

Skin Contact: Wash throughly with soap and water.

Eye Contact: Flush thoroughly with water. See a physician if discomfort persists. **Ingestion:** None. If large quantities are ingested consult your physician.

FIRE FIGHTING MEASURES

Non-flammable and non-hazardous

ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.

PROFILE Products, LLC



Infield Mix

SDS Number: BLM063 Revision Date: 8/21/2018

Page 3

SDS

HANDLING AND STORAGE

Handling Precautions: Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and

reuse as product. If contaminated with other materials, collect in suitable containers.

Storage Requirements: Store in dry area.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use **Equipment:**

NIOSH- approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are

completed.

Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than

Permissible Exposure Limits is recommended.

Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust

exposure to the eves.

Other Protective Equipment: Optional.

Exposure Limits (respirable fraction) in Air: OSHA & MSHA - PEL 10mg/m3

% SiO2 + 2 (8-Hour TWA)

ACGIH - TLV 0.05 mg/cubic meter (8-Hour TWA)

0.05mg/cubic meter (10-Hour TWA, 40-hour work week) NIOSH

Exposure Limits refer to the respirable fraction. PEL means OSHA Permissible Exposure Limit.

TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value.

MSHA means Mine Safety and Health Administration Exposure Limit.

TWA means 8 hour Time Weighted Average.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Red/Brown substrate.

Physical State: Solid.

STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions.

Conditions to Strong Oxiders

Avoldentification:

Materials to Avoldentification: Unreacted polymer monomers

Hazardous Decomposition: None Known **Hazardous Polymerization:** Will not occur.

SDS



Infield Mix

SDS Number: BLM063 Revision Date: 8/21/2018

Page 4 of 4

TOXICOLOGICAL INFORMATION

Inhalation- N.E.

Intravenous- Rat - LD50:15mg/kg Oral - Rat - LD50:3160 mg/kg

ECOLOGICAL INFORMATION

Naturally occuring, inorganic, crystalline, absorbent, clay minerals, such as Attapulgalite and Montmorillonite, are used in a wide variety of commercial, industrial, and consumer applications. Calcium bentonite and sodium bentonite clays, which are composed mostly of monmorillonite, have been listed for many years as Generally Recognized as Safe (GRAS) by the U.S. Food and Drug Administration (FDA) for use in human food and animal feed.

DISPOSAL CONSIDERATIONS

Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

TRANSPORT INFORMATION

Non-hazardous for air, sea and road freight.

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Silica, crystalline quartz (14808607) [n/a%] MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

MASS = MA Massachusetts Hazardous Substances List NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level

OTHER INFORMATION

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).